

3M Science.
Applied to Life.™

Three tapes that handle 90% of your projects.

Duct Tapes. Simplified. We've got this pegged.



3M DT Series Duct Tapes
Right performance. Right price.

Equipped for the day. 8 - 11 - 17 mils.

It's simple. 3M DT Series Duct Tapes in 3 strengths can tackle your everyday tasks. They resist curling, have a consistent unwind, and tear off the roll cleanly for the ultimate in ease of handling and application.

Enlarged photo to show unique texture of 3M DT Series Duct Tapes.

The rolls you always want to keep on hand.

3M DT Series Ducts Tapes offer hand tearability, high tensile strength and conformability.



3M™ All Purpose Duct Tape DT8 *Conformable with instant bond*

The most stretchable of 3M's duct tapes. Its unique design offers high instant adhesion coupled with maximum conformability.

- Great for contoured surfaces and quick labeling
- Tightly woven scrim with high tensile strength for light-duty bundling
- Use for poly abatement, quick repairs, and fast attachments



3M™ Heavy Duty Duct Tape DT11 *Versatility with holding power*

High holding power with a broad attribute performance make this the go-to choice for demanding jobs.

- Sticks immediately and stays on irregular surfaces without lifting—even on plastics
- Polyethylene, water-resistant backing resists wear and light abrasion—great for securing temporary floor coverings
- Long-lasting, moisture-resistant seal in many containment situations, such as attaching heavy poly draping and pipe sealing



3M™ Super Duty Duct Tape DT17 *Super thick for super tough jobs*

Ultra-thick, water-resistant backing resists wear and abrasion yet tears easily by hand.

- Aggressive, natural rubber adhesive grips instantly to a variety of surfaces including metal, glass, plastic and sealed concrete
- Excellent for repairing, seaming and protecting metal parts and surfaces
- Maximum strength for the most demanding applications

Duct Tapes Simplified

Three tapes in three strengths to tackle the bulk of your everyday duct taping tasks.

3M DT Series	Backing Material	Adhesive Type	Thickness (mils)	Tensile strength lb/in (N/100 mm)	Elongation at Break %	Adhesion to Steel oz/in (N/100 mm)	Temperature Range up to 30 minutes	Instant adhesion	Roll size	Color	UPC
Based on ASTM Test Method: D-3652 D-3759 D-3759 D-3330											
3M™ All Purpose Duct Tape DT8	Polyethylene over Cloth Scrim	Synthetic Rubber	8	31 (542)	21%	100 (109.4)	40°F to 130°F	✓	2" x 60 yds (54.8 m)	Silver	0-00-76308-98118-1
3M™ Heavy Duty Duct Tape DT11	Polyethylene over Cloth Scrim	Natural Rubber	11	35 (613)	12%	58 (63.4)	40°F to 130°F	✓	2" x 60 yds (54.8 m)	Silver	0-00-76308-98119-8
										Black	0-00-76308-98120-4
3M™ Super Duty Duct Tape DT17	Polyethylene over Cloth Scrim	Natural Rubber	17	41 (718)	13%	69 (75.5)	40°F to 130°F	✓	2" x 35 yds (32 m)	Black	0-00-76308-98121-1

To see the full line of 3M Duct Tapes and Cloth Tapes, including nuclear grade tape, refer to the 3M Masking and Surface Protection Design Guide. Additional colors are available.



- Patching • Bundling • Reinforcing
- Taping/splicing insulation
- Capping pipe
- Securing conduit ends
- Marking • Labeling
- Temporary repairs
- Hanging polyethylene drapes
- Protecting against sandblast overspray

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
 St. Paul, MN 55144-1000
 800-362-3550 . 877-369-2923 (Fax)
www.3M.com/tape

3M is a trademark of 3M Company.

Printed in U.S.A.
 © 3M 2016
 70-0716-1695-0